
| IPS      |          |       |
|----------|----------|-------|
| SIZE     | <u>A</u> | B     |
| 2"       | 4.5      | 13.63 |
| 2"<br>3" | 4.5      | 14.38 |
| 4"       | 6        | 16.13 |
| 6"       | 7        | 18.13 |
| 8"       | 7.5      | 23    |
| 10"      | 7.5      | 26    |
| 12"      | 9        | 29    |
| 14"      | 9        | 29.88 |
| 16"      | 9        | 30.88 |
| 18"      | 10       | 38.5  |
| 20"      | 10       | 39.5  |
| 22"      | 12       | 42.5  |
| 24"      | 12       | 43.25 |
| 26"      | 14       | 46.5  |
| 28"      | 16       | 58.25 |
| 30"      | 16       | 67.13 |
| 32"      | 16       | 68.25 |
| 34"      | 16       | 69.25 |
| 36"      | 20       | 74.25 |
| 42"      | 20       | 76.75 |
| 48"      | 20       | 79.75 |
| 54"      | 20       | 82.38 |
| 63"      | 20       | 87    |

## TITLE

HDPE FABRICATED 90-deg ELBOWS PLAIN-END/BUTT-FUSE, 5-segment DR9-32.5 FULLY RATED DR7 DE-RATED PE4710







Fittings between 20" and 48" are designed to be fused on a 1648 or smaller field machine, If longer lengths are required, please contact Sandale Utility Products for special requirements.

## DISCLAIMER - PLEASE READ

1) All dimensions approximate, subject to change without notice --Angle tolerance is +/- 2 degrees

--All other dimensions to +/- 1"

2) This drawing only applicable if a copy is referenced at time of order.

--Without a copy of drawing, fitting construction may differ from that shown.

3) Subject to manufacturer's terms and conditions.