# Acrobat<sup>™</sup> 180

Fusion Capability for 63mm to 180mm (2" IPS - 6" DIPS) Pipe



www.sandale.ca



# **OVERVIEW**

The **Acrobat™ 180** is a versatile machine designed for butt fusion of 63mm to 180mm (2" IPS to 6" DIPS) pipe and fittings. The machine offers consistent butt fusion joints — providing a cost-effective alternative to electro-fusion — in an economical, reliable package.

The Acrobat is ideal for in-ditch work. It will convert from 4 to 3 jaws to create a more compact unit and will go even smaller by removing the base plate so that it fuses more easily in confined areas — reducing excavation time.

The fusion carriage is powered by a robust Hydraulic Power Unit (HPU) that is also lightweight and easily portable for quick jobsite setup. This HPU allows the operator to pre-set the facing, heating and fusing pressures individually without having to make adjustments between operations which greatly streamlines the fusion process.

# **FEATURES**

- Small footprint, lightweight
- Toolless conversion of carriage from 4- to 3-jaws for tight work spaces
- Narrow jaws allow fusions for most fittings and flanges
- Hard-anodized aluminum wear surfaces for corrosion resistance
- DataLogger® compatible
- Easy, quick connections to HPU without tools
- Industry-leading 5-Year Warranty
- Single insert design
- Removable upper jaws
- Open-frame HPU design offers easy access for maintenance

# **SPECIFICATIONS**

| ~ | DA | CITY |  |
|---|----|------|--|
|   |    |      |  |

#### MODEL


| CARRIAGE FORCE | VOLTAGE  | HYDRAULIC POWER UNIT | PART NUMBER |  |
|----------------|----------|----------------------|-------------|--|
| Low            | 120V     | Acrobat HPU          | A714801     |  |
|                | 220-240V | Acrobat HPU          | A714802     |  |
|                | 120V     | DynaMc EP HPU        | A714803     |  |
|                | 220-240V |                      | A714804     |  |

| POWER REQUIREMENTS |             | 120V           | 240V           |  |
|--------------------|-------------|----------------|----------------|--|
|                    | Heater      | 1.2 kW         | 0.6 kW         |  |
|                    | Acrobat HPU | .3 HP, 5.9 Amp | .3 HP, 2.4 Amp |  |
|                    | DynaMc HPII | 2.2 HP 14 Amn  | 2.2 HP 7 Amn   |  |

# PLUG TYPE

| 240V:           | CEE 7/7            |
|-----------------|--------------------|
| WEIGHT          |                    |
| 4-Jaw Carriage: |                    |
| 3-Jaw Carriage: | 29 lbs. (13.2 Kg)  |
| Facer:          | 35 lbs. (15.9 Kg)  |
| Heater:         | 14 lbs. (6.4 Kg)   |
| Acrobat HPU:    | 56 lbs. (25.4 Kg)  |
| DynaMc HPU:     | 115 lbs. (52.1 Kg) |

### MAXIMUM GAUGE PRESSURE



# INCLUSIONS

Acrobat 180 package includes fusion machine, facer, heater, insulated heater stand, facer stand, HPU and shipping container. Specifications are subject to change without notice.

