Acrobat™355/400 Size Package

Fusion capability for 355mm and 400mm (14" and 16") polypropylene pipe



www.sandale.ca



OVERVIEW

McElroy's Acrobat machines that feature the QuikFit carriage are size specific and are composed of lightweight, modular components so that the upper and lower jaws can be assembled around the pipe by hand. This eliminates the difficulty of lifting and fitting an entire carriage into a small space. It will fuse pipe in any orientation that is required on plumbing, mechanical and HVAC installations, including vertical and overhead.

The **Acrobat 355/400 Size Package** contains the 355mm and 400mm jaws, heater and facer blade holders. All the of components that are common with other size packages, namely the cylinders and clamp assemblies, carriage skid, facer motor, heater/facer cart, facer stand and HPU are grouped together into a **Core Package**. Both packages are required to assemble the carriage.

The unique design of the heater, facer and jaws has significantly reduced the weight and power requirements for this machine.


The Acrobat 355/400 Size Package will fuse 355mm or 400mm pipe.

FEATURES

- Modular, lightweight carriage and facer assemble around the pipe for optimal close-quarter fusion
- No tools required for assembly or conversion to 3- or 4-jaw unit
- Jaws fit 355 or 400mm pipe no inserts necessary
- Core Package can be used with any Acrobat 355-630 Size Package
- Facer blade orientation allows shavings to fall inside or outside of the pipe
- Stackable shipping container designed to store all machine components

SPECIFICATIONS

uses Pipe Sizes:355mm and 400mm (14" and 16		
MODEL		
A2480101:	. Acrobat 355/400 Size Package + Core Package	
A2480301	Acrobat 355/400 Size Package only	
POWER REQUIREMENTS		
Heater:	200-240V (1,720W), 50/60Hz, 1Ph, 7.8 Amp	
PLUG TYPE		
Heater:	NEMA 6-20	
WEIGHT		
Upper Jaw (355mm/400mm):	6 lbs. (2.7 Kg)/6 lbs. (2.7 Kg)	
Lower Jaw (355mm/400mm):	20 lbs. (9 Kg)/20 lbs. (9 Kg)	
4-Jaw Carriage w/skid (355mm/400mm):	232 lbs. (105 Kg)/237 lbs. (107 Kg)	
3-Jaw Carriage (355mm/400mm):	148 lbs. (67 Kg)/152 lbs. (69 Kg)	
Facer Blade Holder Set:		
Heater:	29 lbs. (13 Kg)	
ON TO MARIE OV		



DIMENSIONS	L W		н
4-Jaw Carriage (355)	55.5" (1,410mm)	28" (711mm)	24.5" (622mm)
3-Jaw Carriage (355)	44" (1,118mm)	28" (711mm)	21.5" (546mm)
4-Jaw Carriage (400)	55.5" (1,410mm)	30" (762mm)	25.5" (648mm)
3-Jaw Carriage (400)	44" (1,118mm)	30" (762mm)	22.5" (572mm)
Heater	41" (1,041mm)	15.5" (394mm)	29" (737mm)

INCLUSIONS

Acrobat 355/400 Size Package includes 355mm and 400mm jaws, heater and facer blade holders. Specifications subject to change without notice.



TO USE A QUIKFIT CARRIAGE:

A Size Package only contains the jaws, heater and facer blade holders for those specific sizes. To assemble and operate the machine, a Core Package (part number A2480201) is required. See reverse for details.



Acrobat[™] Core Package

For use with Acrobat Size Packages from 355-630mm (14"-24") polypropylene pipe



M McELROY

M McELROY

OVERVIEW

McElroy's Acrobat machines that feature the QuikFit™ carriage are size specific and are composed of lightweight, modular components so the upper and lower jaws can be assembled around the pipe by hand. This eliminates the difficulty of lifting and fitting an entire carriage into a small space.

The **Acrobat Core Package** contains all the components that are commonly used with all the **Size Packages**. Specifically, it contains the cylinders and clamp assemblies, carriage skid, facer motor, heater/facer rolling cart, facer stand and HPU. Each Size Package contains the jaws, heater, and facer blade holders. Both Size and Core Packages are required to assemble the carriage.

The patent pending facer is powered by a detachable electric motor for easier maneuverability and can also be taken apart for easier handling and added accessibility. A single HPU powers the heater and facer for all carriage sizes and includes a port for DataLogger® capability. The heater/facer rolling cart allows the user to move everything easily from joint to joint.


The Core Package can be used with any Size Package.


FEATURES


- Modular, lightweight carriage and facer assemble around the pipe for optimal close-quarter fusion
- No tools required for assembly or conversion to 3- or 4-jaw unit
- · Lightweight facer powered by detachable motor for easy maneuverability
- HPU features advanced power management system to minimize peak power draw
- Stackable shipping container designed to store all machine components

SPECIFICATIONS

CAPACITY	
Fuses Pipe Sizes:	355mm - 630mm (14"-24")
MODEL	
A2480201:	Acrobat 355-630 Core Package
POWER REQUIREMENTS	
Facer:	230V (1,700W), 50/60Hz, 1Ph, 7.8 Amp
HPU:	240V (1,700W), 50/60Hz, 1Ph, 20 Amp
Total Power Required (Including he	ater from Size Package):10,620W
PLUG TYPE	
Facer:	NEMA 6-20
HPU:	NEMA L6-30
WEIGHT	
Cylinder Assembly:	
Facer Drive Unit:	75 lbs. (34 Kg)
Facer Motor:	21 lbs. (9.5 Kg)
HPU:	170 lbs. (77 Kg)
HYDRAULICS	
Maximum Gauge Pressure:	3000 PSI (206.8 BAR)







DIMENSIONS	L	w	н
Facer (355 & 400)	40" (1,016mm)	10" (254mm)	33.5" (851mm)
Facer (450 & 500)	40" (1,016mm)	10" (254mm)	35.5" (902mm)
Facer (560 & 630)	40" (1,016mm) 10" (254mm)		38" (965mm)
HPU	32" (813mm)	25.5" (648mm)	19.5" (495mm)

INCLUSIONS

Acrobat 355 – 630 Core Package includes cylinder assemblies, clamp assemblies, carriage skid, facer motor, facer stand, heater/facer rolling cart, HPU and shipping container. Specifications subject to change without notice.



TO USE A QUIKFIT CARRIAGE:

A Core Package contains an HPU, facer and hydraulic cylinders. A Size Package (that includes jaws, heater and facer blade holders) is required. See reverse for details.

