



DISCLAIMER - PLEASE READ

- 1) All dimensions approximate, subject to change without notice
 --Angle tolerance is +/- 2 degrees
 --All other dimensions to +/- 1"
- 2) This drawing only applicable if a copy is referenced at time of order.
 --Without a copy of drawing, fitting construction may differ from that shown.
- 3) Subject to manufacturer's terms and conditions.

| Size | H | L |
|------|------|-------|
| 2 | 5.25 | 13 |
| 3 | 4.75 | 13 |
| 4 | 5.25 | 15 |
| 5 | 7.06 | 19.75 |
| 6 | 7.06 | 20.75 |
| 8 | 7.56 | 23.75 |
| 10 | 7.75 | 26.25 |
| 12 | 9 | 30.75 |
| 14 | 9 | 32 |
| 16 | 9 | 34 |
| 18 | 10 | 38 |
| 20 | 10 | 40 |
| 22 | 12 | 46 |
| 24 | 12 | 48 |
| 26 | 14 | 54 |
| 28 | 20.5 | 69 |
| 30 | 20.5 | 71 |
| 32 | 20.5 | 73 |
| 36 | 20.5 | 77 |
| 40 | 20.5 | 81 |
| 42 | 20.5 | 83 |
| 48 | 20.5 | 89 |

TITLE
 HDPE FABRICATED TEES
 PLAIN-END/BUTT-FUSE,
 DR9-32.5 FULLY RATED
 DR7 DE-RATED
 PE4710

DATE
 8-10-18

Fittings between 20" and 48" are designed to be fused on a 1648 or smaller field machine, If longer lengths are required, please contact Sandale Utility Products for special requirements.