



DISCLAIMER - PLEASE READ

- 1) All dimensions approximate, subject to change without notice
 - -- Angle tolerance is +/- 2 degrees
 - --All other dimensions to +/- 1"
- 2) This drawing only applicable if a copy is refere need at time of order.
 - --Without a copy of drawing, fitting construction may differ from that shown.
- 3) Subject to manufacturer's terms and conditions.

<u>SIZE</u>	<u>A</u>	<u>B</u>
<u>2"</u>	<u>14.5</u>	<u>6.13</u>
<u>3"</u> 4"	<u>14.5</u>	<u>6.13</u>
	16.5	7.5
<u>5"</u>	<u>20.5</u>	<u>7.75</u>
6"	20.5	8
8"	20.25	8.25
10"	20.25	9.25
12"	20	10.63
14"	20	11.25
16"	24	13.75
18"	27	14
20"	35	15
22"	36.5	17
24"	36.5	17.5
26"	36.5	18.5
28"	36.5	20
30"	40.5	20.75
32"	40.5	21.25
34"	40.5	21.5
36"	42.5	24
40"	46.5	27
42"	46.5	27.25
48"	46.5	32.25

TITLE

HDPE FABRICATED WYES PLAIN-END/BUTT-FUSE, DR11-32.5 FULLY RATED DR7 DE-RATED PE4710

DATE

8-10-18

Fittings between 20" and 48" are designed to be fused on a 1648 or smaller field machine, If longer lengths are required, please contact Sandale Utility Products for special requirements.